

HIGH FLOW SYSTEM

Water Softener and Conditioner

Softer smoother skin and hair

Cleaner longer lasting clothes

Cleaner dishes, spotless silverware

Saves up to 75% on soaps and cleaning supplies


Easily clean plumbing fixtures and shower parts

Protect water using appliances

Saves energy



Optional all in one cabinet



A lifetime of soft, conditioned water from HydroSpring™ With over 75 years of combined experience



HIGH FLOW SYSTEN

Water Softener and Conditioner

Double backwash feature for optimum regeneration, cleaning ability, and efficiency

U.V. Protected Heavy Duty Non-Corrosive Noryl BY-PASS



11/4" Connections

U.V. Protected Heavy Duty Non-Corrosive Noryl Valve

> Internals Teflon coated

Water Resistant Cover

Solid State Computer Controlled With L.E.D. Display Step By Step User Friendly Controls

OPTIONAL 2nd Multi Media Tank

Where troublesome water requires additional treatment. Contact your local dealer for more information on adding a 2nd multi-media tank.



range of problems including Iron, Hydrogen Sulfide, Manganese, Heavy Chlorine, Bad Tastes, Bad Colors, or Bad Odors.

Valve is certified by: NSF to NSF/ANSI 44 Cation Exchange Water Softeners

Plain

SYS-HYDROSPRING-R SYS-HYDROSPRING-M

SYS-HYDROSPRING-L

SYS-HYDROSPRING-XL

Tank Shroud

SYS-HYDROSPRING-TS-M SYS-HYDROSPRING-TS-L SYS-HYDROSPRING-TS-XL

Full Weld Jacket

SYS-HYDROSPRING-JKT-R SYS-HYDROSPRING-JKT-M SYS-HYDROSPRING-JKT-L SYS-HYDROSPRING-JKT-XL

Plain Cloth Jacket Black

SYS-HYDROSPRING-NP-PLAIN-M

SYS-HYDROSPRING-NP-PLAIN-L

SYS-HYDROSPRING-NP-PLAIN-XL

SYS-HYDROSPRING-NP-PLAIN-GY-L

SYS-HYDROSPRING-NP-HS-M

SYS-HYDROSPRING-NP-HS-L

SYS-HYDROSPRING-NP-HS-XL

	HYDROSPRING-M	HYDROSPRING-L	HYDROSPRING-XL
VALVE FLOW RATE *	30 GPM	30 GPM	30 GPM
SYSTEM FLOW RATE *	27 GPM	27 GPM	27 GPM
BYPASS SIZE	1"	1"	1.25"
SOFTENING CAPACITY	32,000 Grains	48,000 Grains	64,000 Grains
RESIN VOLUME	1.0 CUFT	1.5 CUFT	2.0 CUFT
MEDIA TANK SIZE DXH	9" x 48"	10" x 54"	12" x 52"
BRINE/SALT TANK SIZE	15" x 35" Square	15" x 35" Square	15" x 35" Square
SHIPPING WEIGHT SYSTEM	98 lbs.	125 lbs.	150 lbs.
SHIPPING WEIGHT BRINE	16 lbs.	17 lbs.	18 lbs.
TANK	*Pressure drop at flow rates listed is less than 15 PSI.		

BUILT TO LAST A LIFETIME!

DISTRIBUTED BY:







